



CERAN HV

DESCRIPTION

Extreme-pressure water resistant high temperature calcium sulfonate complex grease.

APPLICATIONS

CERAN HV is a heavy duty extreme pressure grease, pre-eminently designed for the lubrication of industrial bearings working under high temperatures and high loads in the steel industry. **CERAN HV** is also suitable as EP multi purpose grease, in various other industrial applications where water is in frequent contact with the grease.

SPECIFICATIONS

ISO 6743-9: L-XBFB 1/2

DIN 51 502: KP1/2R -25

Performances meet all Voith VN108 requirements for wet end and dryer part.

ADVANTAGES

Thanks to its very sophisticated formula and performance reserves, **CERAN HV** meets the most stringent industrial requirements set by industrial bearing manufacturers. Excellent thermal and mechanical stability. It regains its original texture after cooling to ambient temperature. Remarkable load resistance thanks to its naturally high extreme pressure and anti-wear properties. Extraordinary water resistance, no significant loss of consistency is observed even with high amounts of water entering the grease. Excellent anti-oxidation and anti-corrosion properties thanks to the very nature of the calcium sulfonates, also in the presence of sea water. **CERAN HV** does not contain lead, or other heavy metals considered harmful to human health and the environment.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com

RECOMMENDATIONS

Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system.

TYPICAL CHARACTERISTICS

| TYPICAL CHARACTERISTICS | METHODS | UNITS | CERAN HV |
|---|-----------------------|--------------------------|---------------------------|
| Soap/thickener | | - | Calcium sulfonate Complex |
| NLGI grade | ASTM D 217/DIN 51 818 | - | 1-2 |
| Color | Visual | - | Brown |
| Appearance | Visual | - | Smooth/tacky |
| Operating temperature range | | °C | - 25 to 180 |
| Penetration at 25°C | ASTM D 217/DIN51 818 | 0.1 mm | 280 - 310 |
| Four ball weld load | ASTM D 2596 | kgf | >400 |
| Anti-rust performance SKF- EMCOR | ISO 11007 | rating | 0-0 |
| Dropping point | IP 396 | °C | >300 |
| Kinematic viscosity of the base oil at 40°C | ASTM D 445 | mm ² /s (cSt) | 420 |

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com