

Fully Synthetic

Kixx D1 C3

*High grade diesel engine oil,
the perfect fit for emission
reduction systems & high durability*

ACEA C2/C3, API SP, MB 229.31

DESCRIPTION

Kixx D1 C3 is a fully synthetic Low SAPS engine oil engineered to comply with the latest ACEA and API international standard, provides unsurpassed lubrication with a wide range of temperature for today's engines operating in severe conditions.

APPLICATIONS

- Diesel-powered vehicles with DPF/CPF/EGR, etc.
- Gasoline and LPG engine vehicles equipped with GDI/T-GDI/DOHC/EFI/VVT, etc.
- Recommended engine oils for vehicles with the following "Performance Specifications"

PERFORMANCE STANDARDS

- API SP, ACEA C2/C3
- MB 229.31

CUSTOMER BENEFITS

- Maximize engine life based on outstanding wear protection
- Extends the service life of emission after treatment systems by prevention of clogging in DPFs and TWCs (Three-Way Catalytic Converters)
- Excellent low temperature fluidity for quick and easy start-ups in cold weather
- Keeps engine clean through outstanding resistance to high temperature varnish and low temperature sludge deposit formation
- Excellent oil consumption control

KEY PROPERTIES

SAE Viscosity	5W-30
Density, kg/L @15°C	0.85
Kinematic Viscosity, mm ² /s @ 40°C	72.5
Kinematic Viscosity, mm ² /s @ 100°C	12.3
Viscosity Index	169
Pour Point, °C	-44
Flash Point, °C	228