

*Semi Synthetic*



# Kixx G SJ

*Gasoline engine oil,  
the perfect fit for smart consumers*

API SJ

## DESCRIPTION

Kixx G SJ is a high quality engine oil designed to meet the requirements of passenger car and light truck engines where API SJ performance is required.

## APPLICATIONS

- Gasoline engines (four-stroke)
- Gasoline engines equipped with emissions control equipment
- Industrial or marine applications using passenger car type gasoline engines
- Diesel Engines (high speed, four-stroke, naturally aspirated)

## PERFORMANCE STANDARDS

- API SJ

## CUSTOMER BENEFITS

### Enhanced Engine Protection

Proven metallo-organic anti-wear additive system forms a protective layer on contact surfaces to control wear. Effective corrosion inhibitors protect against rust and corrosion.

### Trouble-free operation

Special combination of detergent and dispersant additives controls piston and ring deposits that can adversely effect power and performance.

### Long periods between overhauls

Good thermal stability and oxidation resistance combats in-service oil degradation that contributes to filter blocking and sludge formation.

## KEY PROPERTIES

| SAE Viscosity                                   | 5W-30         | 10W-30           | 10W-40              |
|---|---------------|------------------|---------------------|
| Density, kg/L @15°C                             | 0.852         | 0.863            | 0.866               |
| Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C  | 59.5          | 66.8             | 104.8               |
| Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C | 10.2          | 10.1             | 14.8                |
| Viscosity Index                                 | 160           | 140              | 147                 |
| Pour Point, °C                                  | -45           | -42              | -42                 |
| Flash Point, COC, °C                            | 230           | 232              | 234                 |
| Package (Liters)                                | 1, 4, 4T, 200 | 1, 4, 4T, 5, 200 | 1, 3, 4, 5, 20, 200 |