Semi Synthetic

Kixx G SL

Gasoline engine oil, the perfect fit for smart consumers

APISL



DESCRIPTION

Kixx G SL is formulated with synthetic technology base oil and high performance additives. It is optimized to provide outstanding protection and lubricity in all passenger car and light truck gasoline engines.

APPLICATIONS

- All passenger car and light truck four-stroke gasoline engines, both naturally aspirated and turbocharged, including those featuring the most recent valve train and emission
- Suitable for small four-stroke gasoline engines in motorcycle and portable power equipment where engine manufacturers allow the use of conventional passenger car motor oils and do not require a purpose-design lubricant.

PERFORMANCE STANDARDS

API SL

CUSTOMER BENEFITS

- Maximizes engine life through superior wear and deposit control under all operating conditions.
- Provides significant fuel savings by reducing frictional losses.
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity.
- Maintains power and economy by minimizing wear in even the most sophisticated valve train mechanisms, including those with variable valve timing.

KEY PROPERTIES

SAE Viscosity	5W-30	10W-30	10W-40	15W-40
Density, kg/L @15°C	0.849	0.863	0.860	0.864
Kinematic Viscosity, mm ² /s @ 40°C	56.8	65.6	99.5	109.4
Kinematic Viscosity, mm ² /s @ 100°C	10.0	10.0	15.1	15.2
Viscosity Index	165	138	158	145
Pour Point, °C	-45	-45	-42	-39
Flash Point, °C	224	236	246	236
Package (Liters)	4, 200	1, 4, 18, 200	1,3,4,4T,5,20,200	1, 4, 5, 200