

Semi Synthetic



Kixx Ultra 4T Scooter SL

*Top grade engine oil,
the perfect fit for four-stroke scooters*

**API SL
JASO MB Approved**

DESCRIPTION

Kixx Ultra 4T Scooter SL is formulated from Synthetic Technology meeting the requirement of current advanced top-tier engine oil grade of API SL. It is optimized to provide complete scooter engine oil performance especially for fuel efficiency, reducing friction loss and durability.

APPLICATIONS

- All gasoline fueled vehicles
- High performance cars equipped with DOHC, EFI and VVT
- Four-stroke gasoline engines in motorcycles
- Sports Vehicles

PERFORMANCE STANDARDS

- API SL
- 10W-40 / 15W-40 : JASO MB Approved

CUSTOMER BENEFITS

Fuel economy

The wide temperature range capability of the synthetic technology base fluid ensures correct oil viscosity which reduces friction at start-up, and provides maximum lubrication during high temperature operation.

Engine power and maintainability

A reduction in the piston blow-by gas coupled with the oil's anti-sludge characteristics help maintain engine power and cleanliness, which in turn extends the engine's service life.

Oil drainage interval

Excellent oxidation resistance and low volatility will extend oil drainage interval.

All-temperature wear resistance

Advanced non-conventional base oil formula coupled with high performance additive systems and leading edge viscosity index improver delivers excellent shear stability and maximum wear protection in high speed, high temperature driving conditions as well as a rapid, highly effective oil film protection. It also provides component wear resistance during very low temperature cold starts.

KEY PROPERTIES

SAE Viscosity	10W-40	15W-40
Density, kg/L @15°C	0.863	0.871
Kinematic Viscosity, mm ² /s @ 40°C	101.2	114.8
Kinematic Viscosity, mm ² /s @ 100°C	14.8	14.7
Viscosity Index	155	131
Pour Point °C	-42	-39
Flash Point °C	220	242