GRS-7023-0807E

# **Cup Grease**

## Regular Grease

**CUP GREASE** is a regular grease blended from mineral base oils and calcium soap thickeners. It is suitable for lubrication points that are exposed to relatively mild conditions.

#### SPECIAL FEATURE

Good Water Resistance

**CUP GREASE** is resistant to water, so it can be used in locations that are exposed to water.

#### APPLICATIONS

**CUP GREASE** can be used on lubrication points that are exposed to low speeds and light loads.

#### CONTAINERS

180-kg drums, 16-kg pails (No. 3), and 2.5-kg cans x 6 (No. 3)

#### Typical Properties of Cup Grease

Grade		2	3	
Thickener			Calcium soap	Calcium soap
Penetration	(25°C, 60 strokes)		273	236
Dropping point		°C	100	102
Copper strip corrosion	(Room temp., 24 h)		No change	No change
Ash content		mass%	1.2	2.0
Moisture content		mass%	0.7	0.6
Water washout	(38°C, 1 h)	mass%	1.8	0.8

Note: The typical properties are subject to change without notice. (July 2008)



# Handling Precautions

### lacksquare Follow these precautions when handling this product.

	■ <u>Inflammation can occur if grease enters the eyes.</u> When handling this grease, wear <u>protective</u>	
	goggles or take other measures to prevent eye contact.	
! CAUTION	Inflammation can occur if grease comes into contact with skin. When handling this grease, wear	
CAUTION	protective gloves or take other measures to prevent skin contact.	
II	Do not eat this grease. (Swallowing this grease can cause diarrhea and nausea.)	
Handling Precautions	• When opening the container, wear protective gloves in order to avoid cutting your hands.	
Precautions	Keep out of reach of children.	
	• Read the Material Safety Data Sheet (MSDS) for this product before using the product. Obtain	
	the Material Safety Data Sheet from where you purchased the product.	
	■ In case of eye contact, rinse eyes thoroughly with clean water and consult with a physician.	
First Aid	■ In case of skin contact, wash skin thoroughly with soap and water.	
	If this grease is swallowed, do not induce vomiting. Consult with a physician immediately.	
	Do not apply pressure to empty containers. The containers may burst if pressure is applied.	
Disposal of	• Do not weld, heat, drill, or cut the containers. The remaining grease may ignite and the	
<b>Used Grease</b>	containers may explode.	
and	Follow all applicable laws and regulations when disposing of used grease or	
Containers	containers. If you are unsure of the proper disposal methods, consult first with the	
	seller of the grease.	
Storage	Seal the container tightly after use in order to prevent dirt, moisture, etc., from entering the grease.	
Method	Store in a dark location. Avoid direct sunlight.	
PL-50	GRS-7023-0807E	