



Gulf MAX

Passenger Car Motor Oil

Product Description

Gulf MAX is a high quality passenger car motor oil developed for modern, high-output, multi valve, turbocharged & supercharged gasoline powered passenger cars and diesel powered light duty vehicles. All the grades are developed to exceed the performance requirements of API SL.

Features & Benefits

- Better thermo-oxidative stability minimises deposits & sludge build-up facilitating extended oil life
- Active cleaning agents provide engine cleanliness
- Excellent antiwear property minimises engine wear and thereby reduces maintenance cost
- Good low temperature fluidity assists in easy cold starts
- Stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures

Applications

- Recommended for high performance, multi valve, turbocharged & supercharged gasoline powered passenger cars and diesel powered light duty vehicles requiring API SL & API CF quality oils
- SAE 40 viscosity grades are recommended for use in older vehicles where use of single-grade motor oil of API SL or any previous "S" category is recommended

Specifications, Approvals & Typical Properties

Meets the following Specifications		40	10W-30	10W-40	15W-40	20W-50
API CF				X	X	X
Has the following Approvals						
API SL		X	X	X	X	X
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 100 °C, cSt	D 445	14.4	11.10	14.40	14.60	18.40
Viscosity Index	D 2270	101	143	154	130	121
Flash Point, °C	D 92	266	218	224	224	226
Pour Point, °C	D 97	-18	-39	-33	-27	-27
TBN, mg KOH/g	D 2896	7.0	6.60	6.80	7.40	7.80
Density@15°C, Kg/l	D 1298	0.885	0.858	0.885	0.893	0.896
Sulphated Ash, %wt	D 874	0.93	0.83	0.82	0.90	0.90

May 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com