



Gulf Super Duty CF

Commercial Vehicle Engine Oil

Product Description

Gulf Super Duty CF series are heavy duty diesel engine oils developed to meet the requirements of a variety of diesel engines operating under severe conditions. These are formulated from highly refined base stocks and balanced additives to provide effective protection to engines operating under various environments. Gulf Super Duty CF is suitable for use in wide range of on and off-highway applications where such type of lubricant is recommended.

Features & Benefits

- Improved detergency helps reduce deposits and keeps engines cleaner
- Better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening
- Effective antiwear properties protects engine components against wear to offer extended engine life and reduced maintenance costs
- Good corrosion inhibition properties protect against corrosion and wear

Applications

- Turbocharged and naturally aspirated diesel engines of all leading engine manufacturers
- On-highway applications including light and heavy duty applications
- Heavy-duty diesel engines used in mining, construction, agriculture and other off-highway applications
- SAE 10W and SAE 30 grades are suitable for use in some specific hydraulic and transmission application respectively in various heavy duty Dumpers, Dozers, Excavators, Tippers and Cranes used in construction and mining industry where such type of oils are recommended.

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W	30	40	50	15W-40	20W-50	25W-50	25W-60
API CF		X	X	X	X	X	X	X	X
Komatsu Tests – KES 07 802/803/804		X							
Typical Properties									
Test Parameters	ASTM	Typical Values							
Viscosity @ 100 °C, cSt	D 445	5.6	11.00	14.00	18.6	14.4	18.50	18.3	24.2
Viscosity Index	D 2270	104	98	96	97	137	126	115	115
Flash Point, °C	D 92	208	236	244	234	224	242	240	244
Pour Point, °C	D 97	-33	-15	-12	-12	-27	-21	-21	-21
TBN, mg KOH/g	D 2896	10.6	8.60	8.6	6.1	7.2	8.6	8.5	11.1
Density @ 15°C, Kg/l	D 1298	0.895	0.889	0.892	0.901	0.894	0.895	0.904	0.904

February 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com