

TRANSMISSION TM



Gear Oil



USES

- Gear boxes, axies, transfer boxes.
- Specially recommended for highly loaded hypoid gears.
- All types of gears when the MIL-L-2105D specification or API GL-5 required.

PROPERTIES

- High viscosity index.
- High Extreme-Pressure properties.
- Excellent antifoam, anticorrosive and antirust properties.
- Excellent stability in operation.

CHARACTERISTIC

| TRANSMISSION TM | Units | Grade SAE 80W-90 | Grade SAE 85W-90 |
|-------------------------|--------------------|---------------------|---------------------|
| Volumetric mass at 15°C | kg/m ³ | 897 | 906 |
| viscosity at 40°C | mm ² /s | 140 | 199 |
| viscosity at 100°C | mm ² /s | 14.5 | 175 |
| viscosity index | - | 105 | 95 |
| Flash point Cleveland | °C | 208 | 230 |
| Pour point | °C | -27 | -15 |

The typical characteristics mentioned represent mean values.

SPECIFICATIONS

API GL-5
MIL-L2105D

This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.

TRANSMISSION TM 80W-90